



Specifications

GROSS VEHICLE WEIGHT RATING

16,000 GVWR included in base price.

LENGTH

16 ft. nominal, plus gooseneck - 5716.
18 ft. nominal, plus gooseneck - 5718.
20 ft. nominal, plus gooseneck - 5720.
22 ft. nominal, plus gooseneck - 5722.
24 ft. nominal, plus gooseneck - 5724.

WIDTH

7 ft. inside width.

HEIGHT

6 ft.-8 in. inside height.

COUPLER

2-5/16 in. diameter ball-type with adjustable coupler height.

FRONT END

Tapered front.

SIDES

Formed offset sheet and post sections of aluminum with two sizes of punched and double-embossed oval openings. Formed posts on 21" centers.
Choice of Side Patterns: C, D, J, or N.
Full length conspicuity rail ahead and behind fender, which may be used as an outside tie rail.

ROOF

One-piece, stretched aluminum.

REAR DOOR

Style "A" with L.H. Roll-up; and anti-rack lock rod and latch with full width rubber bumper.
Other rear door styles to choose from.

REAR END

Full-width rubber bumper.

FLOOR

BELLY: .110" thick aluminum treadplate with 4 longitudinal corrugations. Crossbars on 12" centers. Aluminum Sub-frame. NOSE: .102" thick flat aluminum.

LANDING GEAR

12,000 lb. drop leg with high-speed crank.

BRAKES

Four-wheel; electric; 2 in. x 12 in.

BRAKES BREAKAWAY KIT

Accidental disconnect safety feature.

AXLES

Two - 7,000 lb. rubber torsion; E-Z Lube hubs.

WHEELS

Must be added to the order.

TIRES

Must be added to the order.

SPARE TIRE CARRIER

Curb side, front drop.

SIDE DOOR

One - With lock rod latch, located on driver's side, with 33" opening.

LIGHTS

Meets or exceeds I.C.C. standards.

INTERIOR LIGHTS

(1) Interior light on 22 ft. models and shorter.
(2) Interior lights on 24 ft. models.

HEADER

Extruded aluminum.

CROWD GATE

Style "A" with outside release latch; punched pan.

NOSE GATE

Style "D" – solid pan type, fold down

RUB RAIL

Extruded aluminum with aluminum extruded running board rail.

FINISH

Steel coated with black Corsol™ anti-corrosive metal treatment; all aluminum left natural.