

**GROSS VEHICLE WEIGHT RATING**

16,000 GVWR included in base price.

LENGTH

16 ft. nominal, plus 7 ft. gooseneck. Available at extra cost in lengths up to and including 32 ft. in 2 ft. increments with corresponding increases in GVWR.

WIDTH

7 ft. inside width. (Additional inside widths of 7.5', 8', and 8.5' are also available)

HEIGHT

6 ft.-8 in. inside height. (Heights greater than 6ft.-8 in. are optional)

COUPLER

2-5/16 in. diameter ball-type with adjustable coupler height.

FRONT END

Tapered front. (Beveled and Radius fronts are optional)

SIDES

Formed offset sheet and post sections of aluminum with two sizes of punched and double-embossed oval openings. Formed posts on 21" centers.
Choice of Side Patterns: A,B,C,D, etc.

ROOF

One-piece, stretched aluminum..

REAR DOOR

Full-width rubber bumper.

FLOOR

.110" thick aluminum tread plate with 4 longitudinal corrugations. Crossbars on 12" centers.

LANDING GEAR

12,000 lb. drop leg with high-speed crank.

BRAKES

Four-wheel; electric

BRAKE BREAKWAY KIT

Accidental disconnect safety feature.

AXLES

OPTIONAL

WHEELS

OPTIONAL

TIRES

OPTIONAL

SPARE TIRE CARRIER

Curb side, front drop.

SIDE DOOR

One - With lock rod latch, located on driver's side.

LIGHTS

Meets or exceeds I.C.C. standards.

INTERIOR LIGHTS

- (1) Interior light on 22 ft. models and shorter.
- (2) Interior light on 24 ft. models and longer.
- (2) Interior light on 22 ft. models and shorter with deck rail.
- (4) Interior light on 24 ft. models and longer with deck rail.

HEADER

Extruded aluminum.

CROWD GATE

Style "A" with outside-release latch; punched pan in trailers 24' and under. Trailers over 24' you must pick a full frame gate.

NOSE GATE

Style "D" – solid pan type, fold down

RUBRAIL

Extruded aluminum with horizontal protective lip.

FINISH

Steel coated with black Corsol™ anti-corrosive metal treatment; all aluminum left natural.