



LENGTH

Overall lengths range from 36'-0" to 53'-0".

WIDTH

Overall width is 102." Inside width is 99" between sides.

HEIGHT

10'-6", 11'-0", 11'-6", 12'-0", 12'-6", 13'-0", and 13'-6" overall outside heights available. 12" front drop. 49" F.W.H.

KING-PIN

6" high assembly with top locking channel. Standard setting: 30" minimum setting: 27" maximum setting: 44". Pin settings deeper than 44" require belly to be shortened. NOTE: 10'-0" nose is standard.

LANDING GEAR

Extruded aluminum telescoping support legs with safety spring lock pins for height adjustment.

FRONT

12" radius front corners with .080" aluminum single wall construction and extruded aluminum rib reinforcing channels, and a 6" aluminum lower front channel. Three-piece aluminum cap with spun corner caps.

SPARE TIRE CARRIER

Optional at extra cost.

SIDES

Formed, offset sheet and post side sections of .080" aluminum with two sides of punched and double-embossed oval openings. Extruded aluminum headers, deck rails, and rub rails. Formed posts on 21" centers.

CLEAN-OUT DOOR

Optional at extra cost.

ACCESS DOOR

Optional at extra cost.

ROOF

One piece translucent roof skin bonded to extruded aluminum roof bows. Aluminum roof is optional.

ROOF

One piece translucent roof skin bonded to extruded aluminum roof bows. Aluminum roof is optional.

FLOOR

.110 aluminum tread plate with 5 corrugations, supported by 6" high extruded aluminum crossbars.

REAR END

Left-hand roll-up with 36" opening, right-hand solid. Full-width rubber bumper, four vertical rubber bumpers, and a stirrup step for trailer access are standard.

REAR COMPARTMENT

6' standard length.

DECKS

Optional at extra cost.

LIGHTS

Front J560 7-way connector mounted in a nose box. Wiring harness is a ultra-blue sealed system. Tail lights are grommet mounted. Sealed LED. Midspan combination turn & clearance lights are grommet mounted sealed LED. Interior lights - 3 total. Exterior lights - 2 groups of 3 individual stop & turn tail lights with one group on each side of rear end. 2 groups of 2 oval, grommet mounted, sealed LED stop & turn lights with one group on each side of upper rear header. Rear I.D. & Marker lights are recessed grommet mounted LED clearance, marker, and license plate lights are standard.

SUSPENSION

Air ride, flange mount, bolt-on to aluminum sub frame.

AXLES

Two: 22,500 lbs. nominal rating standard.

BRAKES

16-1/2" x 7" x 5/8" extended service air brakes, no dust shields. Mandatory FMVSS-121 braking system standard with automatic slack adjusters. ABS is standard equipment using a 2S - 1M system.

HUBS

Dura-Lite, steel with National oil seals, Axilok spindle nuts, and Sentinal hub caps.

DRUMS

Cast steel, outboard mount.

WHEELS

10-hole Hub-Piloted. Eight, 8.25 x 22.5 white steel disc.

TIRES

Eight, 255 x 70R 22.5 Bridgestone R250ED.

FINISH

All steel components are treated with a primer and painted with gray synthetic enamel finish coat to retard rust. King Pin area is undercoated. All aluminum components are left natural.