

**LENGTH**

Overall lengths range from 44'-0" to 53'-0".

WIDTH

Overall width is 102." Inside width is 99" between sides.

HEIGHT

11'-0", 11'-6", 12'-0", 12'-6", 13'-0", and 13'-6" overall heights available. PSADL Drops available in 6", 8", or 12" at belly. All based on 49" F.W.H.

KING-PIN

6" high assembly with top locking channel. Standard setting: 30" minimum setting: 27" PSADL maximum setting: 44". Pin settings deeper than 44" require belly to be shortened.
NOTE: 10'-0" nose is standard.
PSAL has no maximum setting.

LANDING GEAR

Extruded aluminum telescoping support legs with safety spring lock pins for height adjustment.

FRONT

12" radius front corners with .080" aluminum single wall construction and extruded aluminum rib reinforcing channels, and a 6" aluminum lower front channel. Three-piece aluminum cap with spun corner caps.

SPARE TIRE CARRIER

Optional at extra cost.

SIDES

Formed, offset sheet and post side sections of .080" aluminum with two sides of punched and double-embossed oval openings. Extruded aluminum headers, deck rails, and rub rails. Formed posts on 21" centers.

CLEAN-OUT DOOR

Optional at extra cost.

ACCESS DOOR

Optional at extra cost.

ROOF

One piece translucent roof skin bonded to extruded aluminum roof bows. Aluminum roof is optional.

ROOF

One piece translucent roof skin bonded to extruded aluminum roof bows. Aluminum roof is optional.

FLOOR

.110 aluminum tread plate with 5 corrugations, supported by 6" high extruded aluminum crossbars.

REAR END

Left-hand roll-up with 36" opening, right-hand solid. Full-width rubber bumper, four vertical rubber bumpers, and a stirrup step for trailer access are standard.

DECKS

Optional at extra cost.

GATES

Optional at extra cost.

RAMPS

Optional at extra cost.

BULL BAR

Optional at extra cost.

MUD FLAPS

Black Ultra-Rubber, anti-spray type are standard.

LIGHTS

Front J560 7-way connector mounted in a nose box. Wiring harness is a ultra-blue sealed system. Tail lights are grommet mounted. Sealed LED. Midspan combination turn & clearance lights are grommet mounted sealed LED. Interior lights - 3 total. Exterior lights - 2 groups of 3 individual stop & turn tail lights with one group on each side of rear end. 2 groups of 2 oval, grommet mounted, sealed LED stop & turn lights with one group on each side of upper rear header. Rear I.D. & Marker lights are recessed grommet mounted LED clearance, marker, and license plate lights are standard.

SUSPENSION

CB2300 air ride, flange mount, bolt-on SAF Holland flange mounted to aluminum sub frame.

AXLES

Two: 5" round, 22,500 lbs. nominal rating each.

BRAKES

16-1/2" x 7" x 5/8" extended service air brakes, no dust shields. Mandatory FMVSS-121 braking system standard with automatic slack adjusters. ABS is standard equipment using a 2S - 1M system.

HUBS

Dura-Lite, steel with National oil seals, Axilok spindle nuts, and Sentinel hub caps.

DRUMS

Cast steel, outboard mount.

WHEELS

Eight 10-hole hub-piloted, steel disc, white.

TIRES

Eight, Bridgestone radials, PSAL: 11R-24.5 Bridgestone R196 radials. PSADL: size dependant on front drop specified.

FINISH

All steel components are treated with a primer and painted with gray synthetic enamel finish coat to retard rust. King Pin area is undercoated. All aluminum components are left natural.